

## WE OFFER

- Standard Chemical Feed Systems
- Controls / Controllers
- Metering Pumps
- Custom Engineered Systems
- On-Site Oxidant Generation
- Polymer Feed Systems
- Chemical Storage & Accessories
- Booster Skids
- Performance Monitoring Tools
- Transfer Pumps
- Level Monitoring
- Web Based Remote Monitoring
- Instrumentation
- Flow Measurement
- Innovative Accessories

## SPECIALIZED SERVICES

- System Installations
- Start Up & Commissioning
- Contract Maintenance
- Emergency Repairs
- Plant Audits / System Surveys
- Pump/ Accessory Repairs
- Equipment Pool Management
- Equipment Rentals
- Controller Maintenance & Repair

## MARKETS SERVED

- Industrial
- Municipal
- Commercial
- Recreational

1364 Hamilton Parkway  
Itasca, Illinois 60143  
Toll Free 888-200-1800  
Phone: 630-351-9070  
Fax: 630-351-9080

[www.equip-solutions.com](http://www.equip-solutions.com)

## Assmann Chemical Storage Tanks



- ◆ Uniform Quality
- ◆ FDA Compliant Option
- ◆ Superior Impact Resistance
- ◆ Corrosion Resistant
- ◆ Sizes Up to 12,000 Gallons
- ◆ UV Stabilized
- ◆ Multiple Configuration Choices
- ◆ Rapid Delivery

Assmann Corporation manufactures polyethylene tanks and containers with up to 12,000 gallon capacities.

They begin by selecting virgin resins with no re-grind for each application and manufacturing plastic tanks in one-piece construction via rotational molding.

Extensive processing experience and commitment to quality construction provides superior plastic storage tanks for the harshest chemical services.

Assmann Plastic Tanks are designed and molded with a uniform wall thickness that allows the entire surface to cure evenly. Polyethylene tanks are air-cooled for uniform resin cure and improved shrinkage parameters.

Assmann vertical storage tanks (ICT, ACT, IFT) are rotationally molded from your choice of virgin high density crosslink or FDA-compliant linear polyethylene. They are semi-translucent with gallon markers and access openings molded-in. Either is more corrosion and chemical resistant than fiberglass, stainless or mild steel.

Assmann plastic bulk storage tanks are one-piece seamless molded units, designed with wall thicknesses conforming to ASTM D-1998 standards for liquid storage and have narrow diameters for space-saving in-plant use.

These tanks possess excellent low temperature impact resistance and are U.V. stabilized. They are available in natural color or optional blue, green, yellow or black.

The Assmann Poly Double wall tanks (IMT) provide the best protection against hazardous chemical spills into the environment. Inner tank dome overlaps outer tank sidewall to prevent rainwater, snow and debris from entering into the containment basin.

The ability to heat trace and insulate make these tanks perfect for temperature sensitive chemicals. Molded-in lifting lugs (large tanks only) and upper fitting flats are standard. Molded-in lower fitting flats, along with a sturdy Assmann designed bottom outlet, reduce the cost of expensive double wall outlets.

Ask about installation and accessories!