

Internet Gateway with Zero-Touch Connectivity

The all new EquipConnect 2.0 is a state-of-the-art Internet gateway optimized for secure M2M Industrial Internet of Things applications, facilitating data acquisition management, remote monitoring and control of all field endpoint devices. Our Zero-Touch Technology provides secure, intelligent and global connectivity period.

- Full Remote Communications 24/7
- Device Agnostic (Compatible with all controllers)
- Superior security provided by an advanced firewall
- Zero-Touch Technology ensures true plug & play installation and setup
- Pre-activated, pre-programmed carrier agnostic SIM card included
- NEMA 4X Enclosure:
10.5"X 8.5"X 6.25"
- No Proprietary software required

Based on Multi-IMSI (International Mobile Subscriber Identity) technology, EquipConnect 2.0 automatically connects with over 600 carriers around the globe providing worldwide IIoT and M2M connectivity for all of your applications from the network to the endpoint devices, with security in first priority.

EquipConnect 2.0 uses IPSec industry standard data encryption to provide high performance, secure LAN-to-LAN VPN connections with 3DES or AES encryption using IKE and PSK key management.

This powerful security toolbox provides our customers with capabilities to secure their sensitive business-critical data and devices independently within the infrastructure level, e.g. creating VPN's, IP and firewalls as required. Our fully redundant global network, with scalable and robust core carrier network, will make sure you get the highest internet service availability every time with EquipConnect 2.0.



Introducing the new EquipConnect 2.0 communications interface powered by . . .



The EquipConnect 2.0 provides an easy and user-friendly experience, without the need for advanced telecom or cellular engineering skills. This allows for seamless integration with the customer's applications and services. With our Zero-Touch Technology, we do the engineering work for you!

EquipConnect 2.0 Specifications

Input Connections	LAN - RJ45, 10/100 BaseT / RS-232 - DE9
Supply Power	100-240 VAC or 7-32 VDC (upon request)
Environmental Rating	NEMA 4X enclosure with front hinged door
Dimensions	10.5" height X 8.5" width X 6.25" depth
Weight	Approx. 10.5 lbs.
Temperature	Operating: -20F to 120F



EquipConnect 2.0 is powered by **OverSite™**

OverSite™ is a device agnostic, cloud-based data acquisition and process management portal. Users can log on to the highly secure website from anywhere in the world to view, store, input and manipulate all of their process data and critical parameters.



Zero-Touch Technology

This enables EquipSolutions to onboard new clients and gather all of the information needed to build a client profile remotely. We can enter application data, and establish site parameters for all major controllers, without having to be onsite.

Our Zero-Touch Technology approach allows our customers to seamlessly deploy M2M connectivity, including preconfigured low-cost data plans across their entire user base, optimize connectivity costs and fully manage their account base in real-time.

